

Marathon

SPECIFICATIONS

Pavement Crack Routers are only part of the equipment Marathon produces for road maintenance. Contact us for the name of your closest distributor, or for information on our complete line, visit our website at: www.marathonequipmentinc.com



*MAY BE SHOWN WITH OPTIONAL EQUIPMENT

CR300K

PAVEMENT

CRACK

ROUTER

The Marathon Pavement Crack Router offers a more productive method of routing random cracks in asphalt or concrete. The balanced weight distribution, in-line wheels and cutter head, plus extended handle, effectively reduces operator fatigue and allows for safer, smoother, and more accurate maneuverability.

FEATURES & BENEFITS

Models	CR300K	CR260KL	CR380K
Approx. Weight	575lb (261kg)	575lb (261kg)	575lb (261kg)
Engine	30hp Kohler	26hp Kohler, Liquid Cooled	38hp Kohler
Premium Air Filtering System	Standard	Standard	Standard

**Specifications are subject to change without notice.*

- Best balanced router design on the market.
- Sturdy all welded chassis manufactured from ¼" thick steel plate reduces vibration and operator fatigue.
- Standard guard protects fuel tank from damage during use and transportation.
- Powerful and reliable Kohler v-twin engines.
- Three stage air filtration system for optimum performance.
- Convenient electric start, 12V battery and charging system.
- Corrosion proof, durable polypropylene fuel tank.
- Triple banded V belt coupled to optimum sized pulleys provide the perfect router head speed to maximize productivity while extending cutter life.
- Premium wheel assemblies are provided with tapered roller bearings and a 1 ¼" axle for greater durability and ease of operation.
- 12" diameter cutter head fabricated from 1" steel plate.
- Routing is performed by six of our patented carbide tipped router blades strategically positioned on the router head.
- Routing width up to 2".
- Easy access to the router head allows for quick blade changes.
- Handlebar mounted, fingertip operated, linear actuator switch adjusts the cutting depth.
- Indicator plate is provided for cutting depth guidance.
- Engine safety kill switch is conveniently located on the handle control panel.
- Adjustable handle provides a comfortable working position for a variety of different operator heights.
- Large 16" diameter treaded tires provide low rolling resistance and excellent machine control.
- Safety chain guards and rubber flaps provide protection from flying debris.
- Safe loading and unloading is accomplished with the balanced lifting eye.
- Standard paint colour is orange.



NEW
CR260KL Liquid Cooled Router



Easy access for blade replacement



Carbide Tipped Router Blades

Marathon's patented carbide tipped router blades have been proven to outlast ordinary hardened alloy steel cutters and provide a more accurate and consistent cutting depth over a prolonged period of time.



4390 Corporate Drive
Burlington, Ontario, Canada L7L 5R3
Tel: 905-335-0000 Fax: 905-335-9990
www.marathonequipmentinc.com

Distributed By: